



# Longqi International Co.,Ltd

## HT series



High elasticity counter box material, suitable for all kinds of shoes, most use in the sport shoes, working shoes and hiking shoes.

TYPES	
• <b>HT-080/2:</b> 0.75-0.95 mm ± 0.1mm	• <b>HT-080/1:</b> 0.75-0.95 mm ± 0.1mm
• <b>HT-100/2:</b> 0.95-1.15 mm ± 0.1mm	• <b>HT-100/1:</b> 0.95-1.15 mm ± 0.1mm
• <b>HT-120/2:</b> 1.15-1.35 mm ± 0.1mm	• <b>HT-120/1:</b> 1.15-1.35 mm ± 0.1mm
• <b>HT-140/2:</b> 1.35-1.55 mm ± 0.1mm	• <b>HT-140/1:</b> 1.35-1.55 mm ± 0.1mm
• <b>HT-150/2:</b> 1.45-1.65 mm ± 0.1mm	• <b>HT-150/1:</b> 1.45-1.65 mm ± 0.1mm
• <b>HT-180/2:</b> 1.75-2.0 mm ± 0.1mm	
• <b>HT-200/2:</b> 1.95-2.2 mm ± 0.1mm	
• /2(Both side coated with glue)	/1 (Only one side coated with glue)
<b>The above is regular thickness, we can develop different thickness according to the customer's requirement</b>	

TECHNICAL INFORMATION	
• Composition:	Nonwoven Synthetic resins Hot Melt
• Softening point:	100°C
• Sticking temperature:	120-135 °C
• Sticking time:	15 -12seconds
• Open time:	50 seconds
• Pressure:	4 – 5 kg/cm <sup>2</sup>
• Cutting:	Multidirectional

Notice	
• Solvents free, can reduce the production cycle time.	
• Commisure need to stitching.	
• Storage: Avoid direct exposure in the sun.	

SHEET SIZE:	100 x 150 cm
PACKING:	500 sheets per pallet

China factory NanFang industrial zone, Liu Chong Wei community, WanJiang district, DongGuan City, GuangDong China Tel.+86-769-22801730 23390628 Fax.+86-769-22427303 22411369 E-mail:sales@longqiglobal.com Website:www.longqiglobal.com	Vietnam factory: Add: 15DX65Road.7 Quarter.Dinh Hoa Town. Binh Duong new city. Vietnam Tel:+84-0650-3886166 Fax:+84-0650-3886167 E-mail:sales@longqiglobal.com Website:www.longqiglobal.com
---	--